

ICS IE ToughCat 5e S/FTP

Installation cable for tougher environments



Application

Generic Data transmission. This cable is a Cat5e S/FTP cable meant for use as installation (horizontal) cable in tougher electrical and mechanical environment, including ships and offshore units.

Construction

Conductor	: Stranded copper wire Ø 0.22 mm ²
Insulation	: PE, Ø 1.4 mm
Twisting	: 2 Cores to the pair
Lay up	: 4 Pairs
Pair screen	: Al-laminated plastic foil around each pair
Overall screen	: Copper braid, tinned Ø 6,2 mm
Sheath	: Oil resistant, Fire retardant and halogen free LSHF-FR (SHF1)
Marking text	: E.g. "meter" "year" manufacturer ToughCat5 S/FTP 4x2/0,22mm ²

Outer Sheath Colours

Available colours	: Grey
--------------------------	--------

Installation recommendations

Min. Bending Radius during Installation	: 8xD
Min. Bending Radius Fix Installed	: 4xD
Max. Conductor Operating Temperature	: 85°C

Standards applied

IEC 61156-5	Transmission characteristics
EN 50173-1	Generic cabling systems
EN 50288-4-1	Multi-Element Metallic Cables
ISO/IEC 11801	Information technology
IEC 60332-3-24	Flame Retardant
IEC 60754-2	Halogen Free
IEC 61034	Low Smoke
IEC 60811-2-1	Chemical resistance

ICS IE ToughCat 5e S/FTP

Range and Dimensions

Article Code	Nominal diameter outer sheath, mm	MJ/km	kWh/m	Weight of Cable Approx. (Kg/Km)
P82B04P0.22BAZGR1	7.6	515	0,143	65

Electrical properties at 20°C

DC loop resistance		< 158 Ω/km
Resistance unbalance		< 2%
Insulation resistance	(500 V)	> 5000 MΩxkm
Capacitance	at 800 Hz	Nom. 43 nF/km
Capacitance unbalance	(pair to ground)	< 1500 pF/km
Mean Characteristic impedance	@ 100 MHz)	100 ± 5 Ω
Nominal velocity of propagation		0,75c
Propagation delay		< 450 ns/100 m
Delay skew		< 15 ns/100 m
Transfer impedance	At 1 MHz At 10 MHz At 30 MHz	< 10 mΩ/m < 8 mΩ/m < 10 mΩ/m
Coupling attenuation	3	> 85 dB

Nominal Transmission characteristics at 20°C

F (MHz)	Attenuation (dB/100m)	NEXT (dB)	ACR (dB/100m)	Return loss (dB)	PS-NEXT (dB)	PS-ACR (dB/100m)	ELFEXT (dB/100m)	PS-ELFEXT (dB/100m)
1	2,1	90	88	-	87	85	85	82
4	4,0	90	86	27	87	83	85	82
10	6,3	90	84	30	87	81	79	76
16	8,0	90	82	30	87	79	75	72
20	9,0	90	81	30	87	78	73	70
31.25	11,4	90	79	30	87	76	69	66
62.50	16,5	86	70	30	83	67	63	60
100	21,3	83	62	30	80	59	59	56
155.00	24,2	81	57	26	78	54	57	54
200.00	31,5	78	47	25	75	44	53	50
250.00	35,8	77	41	25	74	38	51	48
300.00	47,1	73	26	23	70	23	47	44
600.00	60,1	71	11	20	68	8	44	41

NOTICE

Incore Cables has endeavored to ensure the accuracy of the data in this publication, however we cannot be liable for the consequences of errors or omissions. All data is subject to change without notice. The installer and/or user assumes all liability for the consequences of the installation and/or use of any of our products in contravention of any applicable law, regulation or code.

T : +31 (0)168 468 100

E : sales@incore-cables.com

I : www.incore-cables.com

